



ESTPLY DECK

An anti-slip board for technical flooring

ESTPLY DECK is a birch plywood board with phenolic wire mesh pattern surface. The reverse side is smooth phenolic coating.

The slip resistant surface makes it a safe choice for various technical flooring applications.

ESTPLY DECK can be used in:
Transport industry: Trailers, ship decks, horse boxes, railway wagons.
Building: Scaffolding, loading platforms, pedestrian bridges, warehouses.



Anti-slip



Wear resistant



Strong

ESTPLY DECK

Standard size	1500/1525 mm x 2500/3000/3050/3300 mm			
Size Tolerance	LENGTH/WIDTH	TOLERANCE		
	<1000 mm	±1 mm		
	1000–2000 mm	±2 mm		
	>2000 mm	±3 mm		
Standard Thickness	6.5-> 50 mm			
Thickness Tolerance	NOMINAL THICKNESS (mm)	THICKNESS TOLERANCE		NUMBER OF PLYS
		min. (mm)	max. (mm)	
	4	3.5	4.1	3
	6.5	6.1	6.9	5
	9	8.8	9.5	7
	12	11.5	12.5	9
	15	14.3	15.3	11
	18	17.1	18.1	13
	21	20.0	20.9	15
	24	22.9	23.7	17
	27	25.2	26.8	19
	30	28.1	29.9	21
	35	33.5	35.5	25
	40	38.8	41.2	29
	45	43.6	46.4	33
	50	48.5	51.5	35
Density	kg/m ³ 640-700			
Glue type	Phenol formaldehyde adhesive			
Machining	Estply plywood panels can be machined according to customer specification			
Other Data	Chain of Custody, EN 13986, EN 636 1-2-3 S			
Coating	120-400g			
Edge treatment	Coating related			