## ESTPL



## ESTPLY INTERIOR

Bright and beautiful board for decorative use

ESTPLY INTERIOR is birch plywood board bonded with transparent adhesive. Due to the transparent glue layers, the edge machinings look very clean and natural.

The sanded and smooth surface is very suitable for different types of overlays. ESTPLY INTERIOR is a perfect choice for furniture and joinery.

We at ESTPLY take the carbon emissions seriously. Our birch logs come only from well managed forests, and we process the precious raw material with care and respect.



Great for machining



Strong



Sustainable



## **ESTPLY INTERIOR**

Standard size	1500/1525 mm x 2500/3000/3050/3300 mm 1200/1220/1250 mm x 2400/2440/2500 mm 1200/1220/1250 mm x 3000/3050/3300 mm			
Size Tolerance	LENGTH/WIDTH	TOLERANCE	Ξ	
	<1000 mm 1000–2000 mm >2000 mm	±1 mm ±2 mm ±3 mm		
Standard Thickness	4-> 50 mm			
Thickness Tolerance	NOMINAL THICKNESS (mm)	THICKNESS TOLERANCE NUMBER OF PLIES min. (mm) max. (mm)		
	4 6.5 9 12 15 18 21 24 27 30 35 40 45 50	3.5 6.1 8.8 11.5 14.3 17.1 20.0 22.9 25.2 28.1 33.5 38.8 43.6 48.5	4.1 6.9 9.5 12.5 15.3 18.1 20.9 23.7 26.8 29.9 35.5 41.2 46.4 51.5	3 5 7 9 11 13 15 17 19 21 25 29 32 35
Grades	S, BB, WG, WGE, PQ			
Density	kg/m³ 640-700			
Glue type	Melamine urea glue			
Machining	Estply plywood panels can be machined according to customer specification			
Other Data	DoP link, PEFC certified			
Coating	Declaration of Performance, PEFC certified, FSC Mix Certified, FSC Controlled			
	Wood, EN 13986, EN 636 1-2-3 S			