ESTPLY INTERIOR

Bright and beautiful board for decorative use

ESTPLY INTERIOR is birch plywood board bonded with transparent adhesive. Due to the transparent glue layers, the edge machinings look very clean and natural.

The sanded and smooth surface is very suitable for different types of overlays. ESTPLY INTERIOR is a perfect choice for furniture and joinery.

We at ESTPLY take the carbon emissions seriously. Our birch logs come only from well managed forests, and we process the precious raw material with care and respect.

Great for machining

Strong

Sustainable

ESTPLY INTERIOR

Standard size

1200/1220/1250 mm x 2400/2440/2500 mm
1200/1220/1250 mm x 3000/3050/3300 mm
1500/1525 mm x 2500/3000/3050/3300 mm

Size Tolerance

LENGTH/WIDTH	TOLERANCE
<1000 mm	±1 mm
1000–2000 mm	±2 mm
>2000 mm	±3 mm

Standard Thickness

4-> 50 mm

Thickness Tolerance

NOMINAL THICKNESS (mm)	THICKNESS TOLERANCE min. (mm)	max. (mm)
4	3.5	4.1
6.5	6.1	6.9
9	8.8	9.5
12	11.5	12.5
15	14.3	15.3
18	17.1	18.1
21	20.0	20.9
24	22.9	23.7
27	25.2	26.8
30	28.1	29.9
35	33.5	35.5
40	38.8	41.2
45	43.6	46.4
50	48.5	51.5

Grades

S, BB, WG, WGE, PQ

Density

kg/m³ 640-700

Glue type

Melamine urea glue

Machining

Estply plywood panels can be machined according to customer specification

Other Data

DoP link, PEFC certified

Coating

Transparent melamine 120/120g optional